

easywash365+ everything for the professional car wash

easywash365+ foam lances



Self-service car wash plants offer special programs in order to satisfy the users' needs regarding the cleaning of their cars. By means of an individual range of products the operator tries to stand out from the local competition. Self-service foam cleaning plays an important role in this context. Before effecting high pressure or brush wash strong and sticking foam is coated in order to etch the dirt on the surfaces to be cleaned. The **easywash365+** foam gun which is equipped with an integrated and active foam nozzle ST-75 having an air injector is the ideal tool to spray on mixtures of water and foaming agents as pre-mix which is produced under high pressure. The addition of the foaming agent is executed in the supply room. A separate compressed air connection is not required. As the dosing of air is effected only by the air injector at the foam nozzle there is immediately foam coming out when operating the high pressure gun. All VDA-conform and foama-ble chemicals for washing and cleaning are suitable for an operation.



Foam lance with **easywash365+** gun standard, lance with extension ST-9.1 245 mm and foam head ST-75. Max. 310 bar / 25 l/min / 150 °C

R+M Nr.	D	TYP	☐
202 600 918	1.9 mm	standard	3/8" F swivel



Foam lance with **easywash365+** gun weep version, lance with extension ST-9.1 245 mm and foam head ST-75. Max. 310 bar / 25 l/min / 150 °C

R+M Nr.	D	TYP	☐
202 600 949	1.20 mm	weep	3/8" F swivel
202 600 909	1.35 mm	weep	3/8" F swivel
202 600 917	1.90 mm	weep	3/8" F swivel



Foam lance with **easywash365+** gun freeze stop version, lance with extension ST-9.1 245 mm and foam head ST-75. Max. 310 bar / 25 l/min / 150 °C

R+M Nr.	D	TYP	☐
202 600 929	1.20 mm	freeze stop version	3/8" F swivel
202 600 930	1.35 mm	freeze stop version	3/8" F swivel
202 600 995	1.70 mm	freeze stop version	3/8" F swivel
202 600 919	1.90 mm	freeze stop version	3/8" F swivel

easywash365+ foam sets

By introducing the universally applicable **easywash365+** foam sets we succeeded in enlarging the application possibility of our foam injector family.

The stainless steel injector with high pressure foam lance which is installed via a T-piece between the outlet of the high pressure unit and the original spraying unit is especially designed for the professional cleaning of trucks of shipping or food companies as well as for applications in the industrial foam cleaning.

The connection from injector unit to the high pressure foam lance is realized by

an optionally high pressure hose of up to a length of 40 m. The already existing spraying unit is used for cleaning and rinsing works. Enormous savings of both cleaning agent and time can be achieved as the foam lance has cleaning agent immediately available without switching at the unit or change of equipment.

It is possible to simplify the handling of the construction and to boost efficiency at the same time by integrating two hose reels. This set is suitable for all common high pressure cleaning units for up to 310 bar and max. 90 °C.



easywash365+ foam set: **easywash365+** foam lance standard with foam head ST-75, injector ST-160 (M22 F and 2 x M22 M) with metering valve ST-161, suction hose 1,000 mm and suction filter ST-32. Max. 310 bar / 90 °C

R+M Nr.	D	☐
200 160 720	1.9 mm	3/8" F swivel



easywash365+ foam set: **easywash365+** foam lance standard with foam head ST-75, injector ST-160 (Coupling ST-45-250 nickel-plated brass, plug ST-45-250 zinc-plated steel and M22 M) with metering valve ST-161, suction hose 1,000 mm and suction filter ST-32. Max. 250 bar / 90 °C

R+M Nr.	D	☐
200 160 725	1.9 mm	3/8" F swivel